

# HTP500 Passive Probe Customizable Interconnect Solution



Passive Probe HTP500

## INTRODUCTION

The HTP500 Passive Probe family is a part of our full lineup of customizable interconnect solutions that is a standard, commercial off-the-shelf system engineered to deliver consistent, repeatable, and dependable results.

The Passive Probe provides an industry-leading combination of high bandwidth and high voltage in a rugged, general purpose probing solution, while the small UL-approved probe body and compact head enable access to small geometry circuit elements.

FEATURE	BENEFIT
500 MHz bandwidth & 1,000 V CAT III, 600 V CAT IV	<ul style="list-style-type: none"> <li>A combination of high bandwidth and high voltage reduces the number of probes needed for a variety of applications, simplifying the toolkit and lowering costs</li> </ul>
1X, 10X, & 100X configurations	<ul style="list-style-type: none"> <li>Multiple configurations give the flexibility to choose the passive probe that fits your application</li> </ul>
Third-party certified; exceeds UL61010-31, IEC61010-31	<ul style="list-style-type: none"> <li>Superior product quality and safety greatly reduces risk in high-voltage applications</li> </ul>
Small, compact probe head & body	<ul style="list-style-type: none"> <li>Ability to view small, dense geometry circuit elements with ease</li> <li>Good contact with Device-Under-Test (DUT) ensures correct and accurate probing</li> </ul>

## SUGGESTED APPLICATIONS

- » Low power device services
- » Manufacturing engineering
- » Test research & development
- » Relative low-frequency measurement
- » Low frequency computer & telecom measurements
- » Power supplies
- » Inverter design


# HTP500 Passive Probe Customizable Interconnect Solution

## SPECIFICATIONS & PERFORMANCE


Parameter	TM50-0012-00 (1X)	TM50-0013-00 (10X)	TM50-0014-00 (100X)
Bandwidth	DC to 50 MHz	DC to 500 MHz	DC to 500 MHz
Attenuation Ratio	1:1	10:1	100:1
Max Input Voltage (V)	*CAT III 600V, CAT IV 300V, 50 MHz	*CAT III 1000V, CAT IV 600V, 500 MHz	*CAT III 1000V, CAT IV 600V, 500 MHz
Input Resistance	Impedance of measuring instrument	10 MΩ	100 MΩ
Input Capacitance (pF)	42 pF	12 pF	4.5 pF
Compensation Range	N/A	10 - 25 pF center @ 15 pF	10 - 25 pF center @ 15 pF
Rise Time	Instrument spec + 6 ns	<1 ns	<1 ns
Safety	Conformance to Low Voltage Directive (LVD) 73/23/EEC, Amendment 93/68/EEC;		
Operating Temp.	0 °C to 60 °C, 80% RH		
Storage Temp.	-40 °C to 71 °C		
Operating Altitude	Up to 3,000 m		
Storage Altitude	Up to 15,000 m		

\*Max input voltage frequency dependent, see Voltage Derating Curve.

Voltage Derating Curve



TM50-0013-00 Passive Probe 10:1, 500 MHz (20dB) 1.2 m  
(N5171B @ 0 dB m, MSO-S104A set @ 1 M, avg. 16, w/50 load)



## ORDERING INFORMATION

Model	Description
TM50-0012-00	1X High-Voltage Probe Kit
TM50-0013-00	10X High-Voltage Probe Kit
TM50-0014-00	100X High-Voltage Probe Kit
Kit Includes:	» Probe » Grabber Hook » Insulating Tip Cap » BNC Adapter » RF Ground Spring » Adjusting Screw Driver » Alligator Ground Lead » Instruction Manual



See our line of T&M products at:  
[CarlisleIT.com/markets/test-measurement](http://CarlisleIT.com/markets/test-measurement)

+1 (800) 458.9960  
[TMSales@CarlisleIT.com](mailto:TMSales@CarlisleIT.com)